

Petro-Bailer™

Low-cost passive skimmer with a fixed product inlet.

Application


- ❖ **Passive LNAPL Recovery.**
- ❖ **2 in and larger wells**

Description

The Petro-Bailer™ comprises:

- Top cap with a stainless loop
- Hydrophobic inlet filter element
- Collection reservoir
- Weighted end point

The fixed inlet passive skimmer is made from threaded PVC components and is designed to collect free phase product from 2 in and larger wells. The hydrophobic inlet filter element connects between the body and top cap. The passive skimmer will accommodate water table fluctuations of up to 12 inches. The device will collect water if level fluctuations are greater than 12 in.




SPECIFICATIONS	
Size	61.5 in long x 1.66 in diameter
Volume	0.21 gal
Weight (Net)	3.25 lb
Depth	41.5 in water (minimum for skim)
Materials	PVC body, end point and top. Porous polypropylene fiber element, 12 in stainless steel suspension loop, Buna-N® "O" Rings

ORDERING INFORMATION		
TR-007	2" Petro-Bailer™ (1.66 x 61.5 in)	4 lb
TR-008	Petro-Bailer™ Weighted End	
TR-009	Petro-Bailer™ Replacement Reservoir	
TR-010	Petro-Bailer™ Replacement Hydrophobic Element	
TR-011	Petro-Bailer™ Replacement Top	

www.DurhamGeo.com
Always up to date.

Because we strive to constantly improve our products, our offerings may have changed since the publication of this catalog. Please consult our web site for the latest and most complete information including data sheets, manuals and miscellaneous technical notes.



Save time!
Download data sheets, catalogs, forms and software.

Go to **www.DurhamGeo.com** and select "**Downloads**" from the menu bar on the left, and you should see a page resembling the one shown below.



Save more time by shopping online!

There is a convenient link on our Home page (www.DurhamGeo.com). We even have a Quick Order Form for those who know the part number they wish to order and a quick get-in-and-get-out solution.